



# Mobil™ Coolant Extra Ready Mix -24°C

## Product Description

Mobil Coolant Extra Ready Mixed -24°C is ready for use. Further dilution with water is not recommended. Mobil Coolant Extra Ready Mixed -24°C is a ready to use product that has been pre-mixed with 36% Mobil Antifreeze Extra Glysantin G48® and 64% water. For the preparation of the mixture demineralized water with low electrical conductivity is used, in order to maximize corrosion protection and to minimize

hard water scale deposits in the cooling system. Mobil Coolant Extra Ready Mixed -24°C provides frost protection down to -24°C. Mobil Coolant Extra Ready Mixed -24°C was developed to protect engines against corrosion, overheating and frost damage. It gives a high degree of corrosion protection to engine components such as radiators, cylinder blocks/heads, water pumps and heat exchangers, and avoids deposits. Suitable for energy sector and other industrial applications.

### Official Approvals:

Audi (vehicles built up until 1996, TL 774-C), BMW and BMW motorbikes (vehicles built up until 2019 BMW LC-87), Deutz (DQC CA-14), Eicher (TMTL Part No. 93183798), Fendt, Huerlimann (vehicles built up until 03/2017), Jenbacher (Ta-Nr.1000-0201) 'valid for engines delivered before 01/12/2023', Liebherr (Minimum LH-00-COL3A), Land Rover (vehicles built up from 01/1998 until 01/2005), Lamborghini-Tractors (built up until 03/2017), MAN Energy Solutions (Liste 3.3.7), MAN Truck & Bus (vehicles built up until 11/2011, MAN 324 Typ NF), Maybach (MB-Approval 326.0), Mercedes-Benz Cars (vehicles built up until 04/2014, MB-Approval 326.0), Mercedes-Benz Truck & Bus (vehicles built up until 09/2011, DTFR 29D100), Mini Gasoline Engines (vehicles built up as of 2001, BMW LC-87), Mitsubishi Carisma (vehicles built up from 01/1996 until 01/2004), Mitsubishi Colt (built from 01/2004 until 01/2007), MWM (TR 2091), Porsche (vehicles built up until 1995), Opel / Vauxhall (vehicles built up until 2000, B 040 0240), Rolls-Royce (vehicles built up from 1998, BMW LC-87), Saab (vehicles built up until 2000, 690 1599), Same (vehicles built up until 03/2017), SEAT (vehicles built up until 1996, TL 774-C), SETRA (DTFR 29D100), Skoda (vehicles built up until 1998, TL 774-C), Van Hool, Volkswagen (vehicles built up until 1996, TL 774-C), Volvo Trucks (vehicles built up from 01/1991 until 01/2005, TR 1286083), Zastava

### Recommended for applications requiring:

Alfa Romeo, Atlas, Bentley, Brilliance (Zhonghua), Ferrari, Fiat, Ford, Jaguar, Jinbei (Brilliance), Lada, Lancia, Lotus, Mahindra, Morgan, Toyota

### Directions for use:

- Since the special advantages of Mobil Coolant Extra Ready Mixed -24°C will only be achieved when it is used exclusively, mixing Mobil Coolant Extra Ready Mixed -24°C with other Mobil&nbsp;coolants or products from other producers is not recommended.

### Handling:

- Mobil Coolant Extra Ready Mixed -24°C has a shelf life of at least three years when stored in originally closed, air-tight containers at temperatures of maximum 30°C. Do not use galvanized containers for storage.
- All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

### Shelf life:

- 3 years from date of manufacture.



### Typical Inspections Data:

Freezing Point	below -24 °C
Density @ 20°C	1.055 g/cm <sup>3</sup>